



FEATURES

- Static and dynamic compensation of the radon and thoron solid progenies
- Natural and artificial alpha volumetric activity indication
- On-line spectrometry
- Up to 6 months filter cassette autonomy

ABPM 201L Alpha Beta Particulate Monitor

The ABPM 201L monitor forms part of the RAMSYS product line.

It has been developed to sample air extracted from ventilation ducts or stacks. A double silicon detector (pips) performs the gamma compensation and a radial fin grid limits the scattering of the alpha particles (static compensation) which facilitates the compensation of the radon and thoron solid progenies by the processing algorithms (dynamic compensation).

Operating costs are minimised by the autonomous operation through automatic filter advance management.

APPLICATIONS

- **Effluent release monitoring**
 - Stacks, etc.
- **Radioprotection of workers**
 - Containment atmosphere
 - Control room air, etc.

RELATED MONITORS

- ABPM 201M: mobile version
- ABPM 201S: seismically qualified version
- PING 206S: version with iodine and noble gas
- PIM 206S: version with iodine
- PNG 206S: version with noble gas

radiation monitoring
systems

A Mirion Technologies Division

Featuring:



PHYSICAL CHARACTERISTICS

- Radiation detected: alpha, beta and gamma
- Detector: dual large area silicon
- Filter type: FSLW2 (MILLIPORE)
- Typical energy windows:
 - Alpha: 2 MeV to 10 MeV
 - Beta: 80 keV to 2.5 MeV
 - Gamma: 80 keV to 2.5 MeV
- Typical measurement range:
 - Alpha: 10^{-2} to $3.7 \cdot 10^{+6}$ Bq/m³
($2.7 \cdot 10^{-13}$ to 10^{-4} μ Ci/cc)
 - Beta: 1 to $3.7 \cdot 10^{+6}$ Bq/m³
($2.7 \cdot 10^{-11}$ to 10^{-4} μ Ci/cc)

ENVIRONMENTAL CHARACTERISTICS

- Long term temperature:
+10°C to +40°C (+50°F to +104°F)
- Maximum periodic ambient temperature:
+0°C to +55°C (+32°F to +131°F)
- MTBF: > 50 000 hours, with preventive maintenance
- TID: 100 Gy (10^{+4} rad)

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 35 l/min (1.24 scfm)
- Pressure drop: 100 to 350 mbar (1.45 to 5.07 psi)

MECHANICAL CHARACTERISTICS

- Dimensions: 784 mm x 725 mm x 440 mm
(30.9 in x 28.5 in x 17.3 in)
- Weight: ~ 160 kg (~ 352 lb)
- Color: gray RAL 7030 (decontaminable paint)
- Inlet tube connection: \varnothing 18 mm OD (3/4 in)
- Outlet tube connection: \varnothing 12 mm OD (1/2 in)

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: 1 RS232 and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4-20 mA)

SIGNALING (Applicable to LPDU only)

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC60761, IEC61172, IEC61578
- EMC: 2006/95/CE and 2004/108/CE, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- LPDU or LPU
- Pumping unit
- Monitor wall or floor fixing plate

ACCESSORIES

- Calibration tools
- Software
- USB converters



MIRION
TECHNOLOGIES

Radiation Monitoring Systems
Division

Mirion Technologies (MGPI) SA
BP 1
FR-13113 Lamanon
France

T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

Mirion Technologies (MGPI) Inc
5000 Highlands Parkway
Suite 150
Smyrna, GA 30082
USA

T +1.770.432.2744
F +1.770.432.9179

Mirion Technologies (MGPI H&B) GmbH
Landsberger Strasse 328a
DE-80687 Munich
Germany

T +49 (0) 89515 13-0
F +49 (0) 89515 13 169

www.mirion.com
144098EN-B