



FEATURES

- Static and dynamic compensation of the radon and thoron solid progenies
- Gamma dose rate indication
- Natural and artificial alpha volumetric activity indication
- On-line spectrometry
- Up to 6 months filter cassette autonomy
- Can be used as temporary bypass for ABPM 201S or ABPM 201L when fixed unit is in maintenance with no loss of monitoring capability

ABPM 201M Mobile Alpha Beta Particulate Monitor

The ABPM 201M monitor forms part of the RAMSYS product line.

It has been developed to sample air extracted from ventilation ducts or stacks. A double silicon detector performs the gamma compensation and a radial fin grid limits the scattering of the alpha particles (static compensation) which facilitates the compensation of the radon and thoron solid progenies by the processing algorithms (dynamic compensation).

Operating costs are minimised by the autonomous operation through automatic filter advance management.

APPLICATIONS

- Radioprotection of workers
- Containment atmosphere
- Control room air, etc.
- Operational process monitoring

RELATED MONITORS

- ABPM 201L: "light" version
- ABPM 201S: seismically qualified version
- PING 206S: version with iodine and noble gas
- PIM 206S: version with iodine
- PNG 206S: version with noble gas

radiation monitoring
systems

A Mirion Technologies Division

Featuring:



PHYSICAL CHARACTERISTICS

- Radiation detected: alpha, beta and gamma
- Detector: dual large area silicon
- Filter type: FSLW2 (MILLIPORE)
- Typical energy windows:
 - Alpha: 2 MeV to 10 MeV
 - Beta: 80 keV to 2.5 MeV
 - Gamma: 80 keV to 2.5 MeV
- Typical measurement range:
 - Alpha: 10^{-2} to $3.7 \cdot 10^{+6}$ Bq/m³ ($2.7 \cdot 10^{-13}$ to 10^{-4} μ Ci/cc)
 - Beta: 1 to $3.7 \cdot 10^{+6}$ Bq/m³ ($2.7 \cdot 10^{-11}$ to 10^{-4} μ Ci/cc)

ENVIRONMENTAL CHARACTERISTICS

- Long term temperature:
+10°C to +40°C (+50°F to +104°F)
- Periodic temperature:
-5°C to +55°C (+23°F to +131°F)
- MTBF: > 20 000 hours, with preventive maintenance
- TID: 100 Gy (10^{+4} rad)

PNEUMATIC CHARACTERISTICS

- Standard flow rate: 35 l/min (1.24 scfm)
- Pressure drop: 100 to 350 mbar (1.45 to 5.07 psi)

MECHANICAL CHARACTERISTICS

- Dimensions: 1406 mm x 530 mm x 710 mm
(55.4 in x 21 in x 28 in)
- Weight: ~ 120 kg (~ 265 lb)
- Color: gray RAL 7030 (decontaminable paint)
- Inlet tube connection: \varnothing 12 mm OD (1/2 in)

ELECTRICAL CHARACTERISTICS

- Power supply: 230 Vac – 50 Hz or 120 Vac – 60 Hz
- Data link outputs: 1 RS232 and 2 isolated RS485
- Alarm relays: 3 SPDT relays
- I/O: 2 isolated analog outputs and 1 isolated analog input (0/4-20 mA)

SIGNALING

- Alphanumeric display: measurement, status...
- Sound alarm: buzzer 90 dBA at 1 meter
- Visual alarm: 3 lights (red, yellow, green)

REFERENCE STANDARDS

- Nuclear: IEC60761, IEC61172, IEC61578
- EMC: 2006/95/CE and 2004/108/CE, IEC61000-6-2 and IEC61000-6-4

VERSIONS

- 230 Vac or 120 Vac
- Output dust filter

ACCESSORIES

- Calibration tools
- Software
- USB converters



MIRION
TECHNOLOGIES

Radiation Monitoring Systems
Division

Mirion Technologies (MGPI) SA
Route d'Eygüières
FR-13113 Lamanon
France

T +33 (0) 4 90 59 59 59
F +33 (0) 4 90 59 55 18

Mirion Technologies (MGPI) Inc
5000 Highlands Parkway
Suite 150
Smyrna, GA 30082
USA

T +1 770 432 2744
F +1 770 432 9179

Mirion Technologies (MGPI H&B) GmbH
Landsberger Strasse 328a
DE-80687 Munich
Germany

T +49 (0) 89 515 13 0
F +49 (0) 89 515 13 169

Mirion Commercial (Beijing) Co., Ltd.
Shanghai Jiangchang Commercial Branch
Room 801, 78 Jiangchang SanLu
Zhabei District, Shanghai 200436
PR of China

T +86 21 6180 6920
F +86 21 6180 6924

www.mirion.com
144099EN-E

Since norms, specifications and designs are subject to occasional change, please ask for confirmation of the information given in this publication.

Mirion, Mirion Technologies and MGP Instruments are trademarks and/or registered trademarks of Mirion Technologies, Inc. and/or its affiliates in the United States and/or other countries. All other trademarks are the property of their respective owners.